



Candiwall Technical Data Sheet

Candiwall Brick Slips

Brightstone Buff

All Candiwall brick slips are made from natural clays without using pigments or additives. High performance clays are used to create the best possible finish. Fired at temperatures of 1100°C durability is assured and of course, you can use any of the Candiwall range of slips for internal or external applications.

Properties:

- High compressive strength
- Low Water absorption
- High dimensional stability
- Acid resistant
- 100% recyclable

Certification:

- Certified to European Standard EN14411

	Brick Slip not glazed 220x50x14mm Smooth	Brick Slip not glazed 220x50x14mm Textured	Brick Slip not glazed 220x65x14mm Smooth	Brick Slip not glazed 220x65x14mm Textured	Test Methods
Fire Resistance	Class A1	Class A1	Class A1	Class A1	No need for further testing
Water Absorption	6.4%	6.4%	6.4%	6.4%	EN ISO 10545-3
Thermal Shock	Test Passed	Test Passed	Test Passed	Test Passed	EN ISO 10545-9
Chemical Resistance	Test Passed	Test Passed	Test Passed	Test Passed	EN ISO 10545-13
Freeze / Thaw	Test Passed	Test Passed	Test Passed	Test Passed	EN ISO 10545-12
Stain Resistance	Test Passed	Test Passed	Test Passed	Test Passed	EN ISO 10545-14

Telephone: 01825 723404 E-Mail: sales@candiwall.net Website: www.candiwall.net

DKM Brick Cladding Ltd Bluebell Business Estate, Lewes Road, Uckfield, TN22 3HQ

Packing

Slips are packed in cardboard boxes. Weights and dimensions shown below.

Product	Dimensions	Weight per unit	Weight Per box	Quantities assuming 10mm joint
Stretcher Slips All styles	220x14x65mm	0.36Kgs	22 Kgs	60 slips /m ²
Corner Pistol Slips All Styles	220/105x14x65mm	0.54Kgs	8 Kgs	14 corners per lin mtr
Stretcher Slips All styles	220x14x50mm	0.28Kgs	22 Kgs	76 slips /m ²
Corner Pistol Slips All Styles	220/105x14x50mm	0.54Kgs	8 Kgs	17 corners per lin mtr

BRIGHTSTONE BUFF



Textured surface

This Textured buff / cream slip is a great choice for those who want to create a stunning light coloured facade. The textured finish gives a contrast of light and shade and gives contours to sunlight and reflects the light in differing angles to give a very interesting change to normal flat walls. By using jointing mortar of a complimentary colour, the effect of a homogeneous buff / cream coloured facade can be achieved quite easily.

Sizes Available:-

220mm x 14mm x 65mm = 60 slips per m² and 14 corner slips per lin mtr

220mm x 14mm x 50mm = 76 slips per m² and 17 corner slips per lin mtr

Samples available on request.

Telephone: 01825 723404 E-Mail: sales@candiwall.net Website: www.candiwall.net