



Candiwall Technical Data Sheet

Candiwall Brick Slips

Dallington Red

All Candiwall brick slips are made from natural clays without using pigments or additives. High performance clays are used to create the best possible finish. Fired at temperatures of 1100°C durability is assured and of course, you can use any of the Candiwall range of slips for internal or external applications.

Properties:

- High compressive strength
- Low Water absorption
- High dimensional stability
- Acid resistant
- 100% recyclable

Certification:

- Certified to European Standard EN14411

| | Brick Slip not glazed 220x50x14mm Smooth | Brick Slip not glazed 220x50x14mm Textured | Brick Slip not glazed 220x65x14mm Smooth | Brick Slip not glazed 220x65x14mm Textured | Test Methods |
|----------------------------|---|---|---|---|-----------------------------|
| Fire Resistance | Class A1 | Class A1 | Class A1 | Class A1 | No need for further testing |
| Water Absorption | 6.4% | 6.4% | 6.4% | 6.4% | EN ISO 10545-3 |
| Thermal Shock | Test Passed | Test Passed | Test Passed | Test Passed | EN ISO 10545-9 |
| Chemical Resistance | Test Passed | Test Passed | Test Passed | Test Passed | EN ISO 10545-13 |
| Freeze / Thaw | Test Passed | Test Passed | Test Passed | Test Passed | EN ISO 10545-12 |
| Stain Resistance | Test Passed | Test Passed | Test Passed | Test Passed | EN ISO 10545-14 |

Telephone: 01825 723404 E-Mail: sales@candiwall.net Website: www.candiwall.net

DKM Brick Cladding Ltd Bluebell Business Estate, Lewes Road, Uckfield, TN22 3HQ

Packing

Slips are packed in cardboard boxes. Weights and dimensions shown below.

| Product | Dimensions | Weight per unit | Weight Per box | Quantities assuming 10mm joint |
|-----------------------------------|-----------------|-----------------|----------------|--------------------------------|
| Stretcher Slips All styles | 220x14x65mm | 0.36Kgs | 22 Kgs | 60 slips /m ² |
| Corner Pistol Slips All Styles | 220/105x14x65mm | 0.54Kgs | 8 Kgs | 14 corners per lin mtr |
| Stretcher Slips All styles | 220x14x50mm | 0.28Kgs | 22 Kgs | 76 slips /m ² |
| Corner Pistol Slips All Styles | 220/105x14x50mm | 0.54Kgs | 8 Kgs | 17 corners per lin mtr |

DALLINGTON RED



Textured surface

One of our most popular choices, the Dallington Red offers a warmth of colour and a rustic textured finish that lends itself to most build types. Whether your project is contemporary architecture or of a more traditional or classical nature, the Dallington Red has proved to be very popular.

Sizes Available:-

220mm x 14mm x 65mm = 60 slips per m² and 14 corners per lin mtr

220mm x 14mm x 50mm = 76 slips per m² and 17 corners per lin mtr

Samples available on request

Telephone: 01825 723404 E-Mail: sales@candiwall.net Website: www.candiwall.net